




LED Flood Light Quotation (A B C Series)




50w



70w



100w



120w



150w/200w



240w

Model NO.	Power	Input Voltage	Chip Brand	Chip QTY	luminous Flux (lm)	Beam Angle	IP Degree	Lamp SIZE (MM)
HS-FL1W10-A	10w	AC85-265V	Bridgelux chip	1*10W	950-1010LM	118°*106°	IP65	L179*W133*H59
HS-FL2W20-A	20w	AC85-265V	Bridgelux chip	1*20W	1900-2020LM	110°*90°	IP65	L201*W172*H80
HS-FL3W30-A	30w	AC85-265V	Bridgelux chip	1*30W	2850-3030LM	118°*90°	IP65	L201*W172*H80
HS-FL4W50-A	50w	AC85-265V	Bridgelux chip	1*50W	4750-5050LM	113°*98°	IP65	L253*W200*H98
HS-FL5W70-A	70w	AC85-265V	Bridgelux chip	1*70W	6650-7070LM	119°*90°	IP65	L291*W250*H116
HS-FL5W80-A	80W	AC85-265V	Bridgelux chip	1*80W	7600-8080LM	90°*120°	IP65	L360*W280*H120
HS-FL5W100-A	100w	AC85-265V	Bridgelux chip	1*100W	9500-10100LM	108°*97°	IP65	L291*W250*H116
HS-FL5W120-A	120w	AC85-265V	Bridgelux chip	2*60W	11400-12120LM	122°*107°	IP65	L309*W250*H192
HS-FL6W150-A	150w	AC90-295V	Bridgelux chip	2*75W	14250-15150LM	122°*100°	IP65	L315*W310*H187
HS-FL6W180-A	180w	AC90-295V	Bridgelux chip	2*90W	18000-18500LM	121°*101°	IP65	L315*W310*H187
HS-FL7W200-A	200w	AC90-295V	Bridgelux chip	2*100W	19900-20400LM	121°*100°	IP65	L375*W310*H187
HS-FL7W240-A	240w	AC90-295V	Bridgelux chip	4*60W	24000-24300LM	128°*101°	IP65	L375*W310*H187

Calle Porcel N°214, Urb. María Isabel, Arequipa - Arequipa | Perú

Tel.: (054) 507474 | RPC 987090104 | RPM #958343859

E-mail: ventas@energiainnovadora.com | www.energiainnovadora.com