

Technical specifications :

Model	LS0512EU	LS1012EU	LS1024EU	LS2024EU
Nominal system voltage	12VDC		12/24VDC	
Rated battery current	5A	10A	10A	20A
Max. battery voltage	16V		32V	
Max. PV open circuit voltage	30V		50V	
Equalize charging voltage	Gel: ----, Sealed: 14.6V, Flooded: 14.8V			
Boost charging voltage	Gel: 14.2V, Sealed: 14.4V, Flooded: 14.6V			
Float charging voltage	Gel / Sealed / Flooded:13.8V			
Low voltage reconnect voltage	Gel / Sealed / Flooded:12.6V			
Low voltage disconnect voltage	Gel / Sealed / Flooded:11.1V			
USB output	5VDC/1.2A			
Charge circuit voltage drop	≤0.26V			
Discharge circuit voltage drop	≤0.15V			
Self-consumption	≤6mA			
Temp. compensation	-5mV/°C/2V (ref)			
Overall dimension(mm)	109.7x65.5x20.8	120.3x67x21.8	120.3x67x21.8	148x85.6x34.8
Mounting dimension	100.9mm	111.5mm	111.5mm	138mm
Mounting hole size	Φ4.5	Φ4.5	Φ4.5	Φ4.5
Terminal	2.5mm ²	4mm ²	4mm ²	6mm ²
Weight	95g	103g	102g	179.6g
Working temperature	-35°C ~ +55°C			
Storage temperature	-35°C ~ +80°C			
Humidity	≤95% N.C.			
Enclosure	IP20			